






SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** SX GLUE SCREWS
-
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Sealant
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SIROFLEX LIMITED
Dodworth Business Park
Dodworth, Barnsley,
South Yorkshire S75 3SP
Tel: 01226 771600
Fax: 01226 771601
- **Further information obtainable from:**
info@siroflex.co.uk www.siroflex.co.uk
- **1.4 Emergency telephone number:**
Tel: 01226 771600 (Office Hours Only)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
 -  GHS02 flame
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
 -  GHS07
STOT SE 3 H336 May cause drowsiness or dizziness.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
 -  Xi; Irritant
R38: Irritating to skin.
 -  F; Highly flammable
R11: Highly flammable.
 -  N; Dangerous for the environment
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67: Vapours may cause drowsiness and dizziness.
- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)

Den Braven**Safety data sheet**
according to 453/2010/EC

Date: 01.12.2014

Replaces: 22.05.2014

Ref: 0308.1.DB/DL

Trade name: SX GLUE SCREWS

(Contd. of page 1)

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· 2.2 Label elements**· Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms

GHS02 GHS07

· Signal word Danger**· Hazard statements**

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P240 Ground/bond container and receiving equipment.

P242 Use only non-sparking tools.

P273 Avoid release to the environment.

P243 Take precautionary measures against static discharge.

P271 Use only outdoors or in a well-ventilated area.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****· 3.2 Chemical characterization: Mixtures****· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

(Contd. on page 3)

GB

Den Braven

Safety data sheet according to 453/2010/EC









Date: 01.12.2014

Replaces: 22.05.2014

Ref: 0308.1.DB/DL

Trade name: SX GLUE SCREWS

(Contd. of page 2)

CAS: 92045-53-9 EINECS: 295-434-2 Reg.nr.: 01-2119666169-27-xxxx	Naphtha (petroleum), hydrodesulfurized light dearomatized  R67 	10-<30%
CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light  R67 	5-<10%
CAS: 110-82-7 EINECS: 203-806-2	cyclohexane  R67 	<1.0%
CAS: 110-54-3 EINECS: 203-777-6 Reg.nr.: 01-2119480412-44-xxxx	n-hexane  R67 Repr. Cat. 3 	<1.0%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation

(Contd. on page 4)

**Den Braven****Safety data sheet**
according to 453/2010/EC

Date: 01.12.2014

Replaces: 22.05.2014

Ref: 0308.1.DB/DL

Trade name: SX GLUE SCREWS

(Contd. of page 3)

· 6.2 Environmental precautions:

- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Pick up mechanically.
- Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage**· 7.1 Precautions for safe handling**

- Ensure good ventilation/exhaustion at the workplace.
- Use only in well ventilated areas.

· Information about fire - and explosion protection:

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities**· Storage:****· Requirements to be met by storerooms and receptacles:** Store in a cool location.**· Information about storage in one common storage facility:** Not required.**· Further information about storage conditions:**

- Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection****· Additional information about design of technical facilities:** No further data; see item 7.**· 8.1 Control parameters****· Ingredients with limit values that require monitoring at the workplace:****110-82-7 cyclohexane**

WEL	Short-term value: 1050 mg/m ³ , 300 ppm Long-term value: 350 mg/m ³ , 100 ppm
-----	--

· Additional information: The lists valid during the making were used as basis.**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

(Contd. on page 5)

GB

Den Braven

Safety data sheet according to 453/2010/EC

Date: 01.12.2014

Replaces: 22.05.2014

Ref: 0308.1.DB/DL

Trade name: SX GLUE SCREWS

(Contd. of page 4)

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Pasty
Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not determined.

- **pH-value:** Undetermined.

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

- **Flash point:** < 0 °C

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** Undetermined.

- **Decomposition temperature:** Not determined.

- **Self-igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

Lower:	Undetermined.
Upper:	Undetermined.

(Contd. on page 6)

**Den Braven****Safety data sheet**
according to 453/2010/EC

Date: 01.12.2014

Replaces: 22.05.2014

Ref: 0308.1.DB/DL

Trade name: SX GLUE SCREWS

(Contd. of page 5)

· Vapour pressure:	Undetermined.
· Density at 20 °C:	1.3 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC (EC)	32.95 %
VOC (EC)	428.3 g/l
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:****110-82-7 cyclohexane**

Oral | LD50 | 12705 mg/kg (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.

(Contd. on page 7)

Den Braven

Safety data sheet according to 453/2010/EC

Date: 01.12.2014

Replaces: 22.05.2014

Ref: 0308.1.DB/DL

Trade name: SX GLUE SCREWS

(Contd. of page 6)

- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations




- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other dangerous substances
-----------	--

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1133
- **14.2 UN proper shipping name**
- **ADR** 1133 ADHESIVES
- **IMDG** ADHESIVES (Naphtha (petroleum), hydrodesulfurized light dearomatized, Naphtha (petroleum), hydrotreated light), MARINE POLLUTANT
- **IATA** ADHESIVES
- **14.3 Transport hazard class(es)**
- **ADR, IATA**
- 
- **Class** 3 Flammable liquids.
- **Label** 3
- **IMDG**
- 

- **Class** 3 Flammable liquids.
- **Label** 3

(Contd. on page 8)

**Den Braven****Safety data sheet**
according to 453/2010/EC

Date: 01.12.2014

Replaces: 22.05.2014

Ref: 0308.1.DB/DL

Trade name: SX GLUE SCREWS

(Contd. of page 7)

· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	Product contains environmentally hazardous substances: cyclohexane Yes Symbol (fish and tree)
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Flammable liquids. 33 F-E,S-D
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG	
· Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN1133, ADHESIVES, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H224 Extremely flammable liquid and vapour.
- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- R11 Highly flammable.

(Contd. on page 9)

**Den Braven****Safety data sheet**
according to 453/2010/EC

Date: 01.12.2014

Replaces: 22.05.2014

Ref: 0308.1.DB/DL

Trade name: SX GLUE SCREWS

(Contd. of page 8)

- R38 Irritating to skin.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62 Possible risk of impaired fertility.
R65 Harmful: may cause lung damage if swallowed.
R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Product safety department.

· **Contact:** Pascal Timmermans / Kees van Bommel

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 1: Flammable liquids, Hazard Category 1

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· *** Data compared to the previous version altered.**

GB