



## DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) No 305/2011  
(Construction Product Regulation)

DoP \_ [EN] \_ 001 \_ No S11001001-0029

1. Unique identification code of product-type:  
**SX PAINTERS CAULK IT 310ML**
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):  
**Batch number: See product packaging**
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:  
**EN 15651-1: F-EXT-INT  
CLASS 7,5P  
Sealants for façade elements**
4. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):  
**SIROFLEX LIMITED, DODWORTH BUSINESS PARK, DODWORTH, BARNSELY, SOUTH YORKSHIRE, S75 3SP**
5. Name and contact address of the authorized representative whose mandate covers the task specified in Article 12 (2): not relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 3  
System 3 for reaction to fire**
7. In case of declaration of performance concerning a construction product covered by a harmonized standard:  
**The notified body SKZ – TeConA GmbH (1213) performed the initial type testing according to EN 15651-1 and reaction to fire under System 3 and issued: a test report.**
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: not relevant

DODWORTH BUSINESS PARK  
DODWORTH BARNSELY  
SOUTH YORKSHIRE S75 3SP

**SX PAINTERS CAULK IT 310ML - DoP \_ [EN] \_ 001 \_ No S11001001-0029****9. Declared performance:**

**Conditioning:** Procedure A (according to ISO 8339)  
**Substrate:** Mortar M2 (without primer)

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 25 %	
Tensile properties after immersion in water (at 23°C)	≥ 25 %	
Durability	Pass	

(\*) See material safety data sheet  
NPD: No Performance Determined

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not relevant

**10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for and on behalf of the manufacturer by:



**Ashley Greenwood**  
HSE Manager  
Siroflex Limited

18/06/2014