



SAFETY DATA SHEET
PRE-MIX WOODFILLER 300G ALL COLOURS

Page: 1
Compilation date: 18/09/2013
Revision date: 14/12/2017
Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PRE-MIX WOODFILLER 300G ALL COLOURS

Product code: 31140 to 31146

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Wood Repair

1.3. Details of the supplier of the safety data sheet

Company name: Chemfix Products Limited

Mill Street East

Dewsbury

West Yorkshire

WF12 9BQ

United Kingdom

Tel: +44 (0)1924 453886

Fax: +44 (0)1924 458995

Email: sds@chemfix.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1924 431679

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Skin Sens. 1: H317

Most important adverse effects: May cause an allergic skin reaction. Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

Hazard pictograms: GHS07: Exclamation mark



Signal words: Warning

Precautionary statements: P264: Wash skin thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace.

[cont...]

SAFETY DATA SHEET

PRE-MIX WOODFILLER 300G ALL COLOURS

Page: 2

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

Other hazards: Not applicable.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

VINYL TOLUENE - REACH registered number(s): 01-21196222074-50-0000

EINECS	CAS	PBT / WEL	CLP Classification	Percent
246-562-2	25013-15-4	-	Acute Tox. 4: H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315	3-10%

DIBENZOYL PEROXIDE - REACH registered number(s): 01-2119511472-50-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-327-6	94-36-0	-	Eye Irrit. 2: H319; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Org. Perox. EF: H242; Skin Sens. 1: H317	1-3%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

[cont...]

SAFETY DATA SHEET
PRE-MIX WOODFILLER 300G ALL COLOURS

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

[cont...]

SAFETY DATA SHEET
PRE-MIX WOODFILLER 300G ALL COLOURS

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIBENZOYL PEROXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m ³	-	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory protection is recommended. Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Wear solvent proof gloves. Nitrile gloves. Viton gloves. Recommended thickness of material >0.4 mm. Breakthrough time of the glove material > 8 hours. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Various

Odour: Characteristic odour

Evaporation rate: Negligible

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Viscous

Relative density: 1.9

VOC g/l: 2.26

9.2. Other information

Other information: Solid suspension - classified as non-flammable according to results from Test N.1 test method for readily combustible solids.

[cont...]

SAFETY DATA SHEET
PRE-MIX WOODFILLER 300G ALL COLOURS

Page: 5

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DIBENZOYL PEROXIDE

ORL	RAT	LD50	2000	mg/kg
VAPOURS	RAT	LD50	24.3	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

[cont...]

SAFETY DATA SHEET
PRE-MIX WOODFILLER 300G ALL COLOURS

Page: 6

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Grey Catalyst Comp. B

Species	Test	Value	Units
FISH	48H EC50	>7	mg/l
Daphnia magna	48H EC50	>11	mg/l
FISH	96H LC50	>100	mg/l
ALGAE	72H ErC50	>60	mg/l

Hazardous ingredients:

DIBENZOYL PEROXIDE

ALGAE	72H ErC50	0.0711	mg/l
Daphnia magna	48H EC50	0.110	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	0.0602	mg/l

12.2. Persistence and degradability

Persistence and degradability: Rapidly biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Insoluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 04 09

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

[cont...]

SAFETY DATA SHEET

PRE-MIX WOODFILLER 300G ALL COLOURS

Page: 7

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Active Oxygen Content of Catalyst Component 0.99%

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H242: Heating may cause a fire.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.