



APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Issue date: 12-05-2021 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : APLEX AQUA WOODCOAT INDU S BASE WHITE
Product code : 17-0695-110
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use

Title	Use descriptors
	PC9a, PROC7

Full text of use descriptors: see section 16

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Anker Stuy Verven B.V.
Hellingwal 1
NL-8407 EM Terwispel - Nederland
T +31(0)513-465000
info@ankerstuy.nl - www.ankerstuy.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixtures/Substances: SDS EU > 2015: According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

Skin sensitisation, Category 1 H317

Carcinogenicity Not classified

Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP)

: Warning

Contains

: cobalt neodecanoate; reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1); 2-methylisothiazol-3(2H)-one; reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -poly(oxyethylene); Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Hazard statements (CLP)

: H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P321 - Specific treatment (see supplemental first aid instruction on this label).

EUH-statements

: EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.	Classification according to Regulation (EC) No. 1272/2008 [CLP]
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] substance with national workplace exposure limit(s) (ES, FR, PL)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-002 REACH-no: 01-2119489379-17	10 – 25	Carc. 2, H351
silicon dioxide, amorphous substance with national workplace exposure limit(s) (DE)	CAS-No.: 7631-86-9 EC-No.: 231-545-4 REACH-no: 01-2119379499-16	1 – 2,5	Not classified
triethylamine substance with national workplace exposure limit(s) (DE, ES, FR, NL, PL); substance with a Community workplace exposure limit	CAS-No.: 121-44-8 EC-No.: 204-469-4 EC Index-No.: 612-004-00-5 REACH-no: 01-2119475467-26	0,1 – 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	Conc.	Classification according to Regulation (EC) No. 1272/2008 [CLP]
MONO PROPYLENE GLYCOL substance with national workplace exposure limit(s) (PL)	CAS-No.: 57-55-6 EC-No.: 200-338-0	0,1 – 1	Not classified
(2-methoxymethylethoxy)propanol substance with national workplace exposure limit(s) (DE, ES, FR, NL, PL); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2 REACH-no: 01-2119450011- 60	0,1 – 1	Not classified
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	EC-No.: 400-830-7 EC Index-No.: 607-176-00-3 REACH-no: 01-0000015075- 76	0,1 – 1	Skin Sens. 1, H317 Aquatic Chronic 2, H411
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	CAS-No.: 1065336-91-5 EC-No.: 915-687-0 REACH-no: 01-2119491304- 40	0,1 – 1	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 (M=0)
cobalt neodecanoate	CAS-No.: 27253-31-2 EC-No.: 248-373-0 REACH-no: 01-2119970733- 31	0,1 – 1	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317 Repr. 2, H361 Aquatic Chronic 3, H412
3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate substance with national workplace exposure limit(s) (DE)	CAS-No.: 55406-53-6 EC-No.: 259-627-5 EC Index-No.: 616-212-00-7 REACH-no: 01-2120762115- 60	< 0,1	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation:dust,mist), H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve substance with national workplace exposure limit(s) (DE, ES, FR, NL, PL); substance with a Community workplace exposure limit	CAS-No.: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0 REACH-no: 01-2119475108- 36	< 0,1	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Irrit. 2, H315
2-phenoxyethanol substance with national workplace exposure limit(s) (DE, PL)	CAS-No.: 122-99-6 EC-No.: 204-589-7 EC Index-No.: 603-098-00-9 REACH-no: 01-2119488943- 21	< 0,1	Acute Tox. 4 (Oral), H302 Acute Tox. Not classified (Inhalation:dust,mist) Eye Irrit. 2, H319
kaolin substance with national workplace exposure limit(s) (PL)	CAS-No.: 1332-58-7 EC-No.: 310-194-1	< 0,1	Not classified
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5	< 0,1	Acute Tox. 2 (Inhalation), H330 Acute Tox. 2 (Dermal), H310 Acute Tox. 3 (Oral), H301 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	Conc.	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-methylisothiazol-3(2H)-one	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9 REACH-no: 01-2120764690-50	< 0,1	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410

Specific concentration limits		
Name	Product identifier	Specific concentration limits
triethylamine	CAS-No.: 121-44-8 EC-No.: 204-469-4 EC Index-No.: 612-004-00-5 REACH-no: 01-2119475467-26	(1 ≤C ≤ 100) STOT SE 3, H335
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5	(0,0015 ≤C ≤ 100) Skin Sens. 1A, H317 (0,06 ≤C < 0,6) Skin Irrit. 2, H315 (0,6 ≤C ≤ 100) Skin Corr. 1C, H314
2-methylisothiazol-3(2H)-one	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9 REACH-no: 01-2120764690-50	(0,0015 ≤C ≤ 100) Skin Sens. 1A, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
-------------------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve (111-76-2)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	2-Butoxyethanol
IOEL TWA	98 mg/m ³
IOEL TWA [ppm]	20 ppm
IOEL STEL	246 mg/m ³

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve (111-76-2)	
IOEL STEL [ppm]	50 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
France - Occupational Exposure Limits	
Local name	2-Butoxyéthanol (Butylglycol)
VME (OEL TWA)	49 mg/m ³
VME (OEL TWA) [ppm]	10 ppm
VLE (OEL C/STEL)	246 mg/m ³
VLE (OEL C/STEL) [ppm]	50 ppm
Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n°2021-434)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	2-Butoxyethanol
AGW (OEL TWA) [1]	49 mg/m ³
AGW (OEL TWA) [2]	10 ppm
Peak exposure limitation factor	2(l)
Remark	EU;DFG;H;Y
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	2-Butoxyethanol
BLV	150 mg/g creatinine Parameter: Butoxyessigsäure (nach Hydrolyse) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende, c) bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten - Festlegung/Begründung: 11/2016 DFG
Regulatory reference	TRGS 903
Netherlands - Occupational Exposure Limits	
Local name	2-Butoxyethanol
MAC-TGG (OEL TWA)	100 mg/m ³
MAC-15 (OEL STEL)	246 mg/m ³
Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2021
Poland - Occupational Exposure Limits	
Local name	2-Butoksyetanol (butoksyetylowy alkohol)
NDS (OEL TWA)	98 mg/m ³
NDSch (OEL STEL)	200 mg/m ³
Remark (PL)	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve (111-76-2)	
Spain - Occupational Exposure Limits	
Local name	2-Butoxietanol (Butil cellosolve; Éter monobutílico del etilenglicol)
VLA-ED (OEL TWA) [1]	98 mg/m ³
VLA-ED (OEL TWA) [2]	20 ppm
VLA-EC (OEL STEL)	245 mg/m ³
VLA-EC (OEL STEL) [ppm]	50 ppm
Notes	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo), VLB® (Agente químico que tiene Valor Límite Biológico).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
Spain - Biological limit values	
Local name	2-Butoxietanol (Butil cellosolve; Éter monobutílico del etilenglicol)
BLV	200 mg/g creatinine Parámetro: Ácido butoixiacético - Medio: Orina - Momento de muestreo: Final de la jornada laboral - Notas: Con hidrólisis
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
2-phenoxyethanol (122-99-6)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	2-Phenoxyethanol
AGW (OEL TWA) [1]	5,7 mg/m ³
AGW (OEL TWA) [2]	1 ppm
Peak exposure limitation factor	1(I)
Remark	DFG;Y;11
Regulatory reference	TRGS900
Poland - Occupational Exposure Limits	
Local name	2-Fenoksyetanol
NDS (OEL TWA)	230 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286
triethylamine (121-44-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Triethylamine
IOEL TWA	8,4 mg/m ³
IOEL STEL	12,6 mg/m ³
IOEL STEL [ppm]	3 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
France - Occupational Exposure Limits	
Local name	Triéthylamine
VME (OEL TWA)	4,2 mg/m ³

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

triethylamine (121-44-8)	
VME (OEL TWA) [ppm]	1 ppm
VLE (OEL C/STEL)	12,6 mg/m ³
VLE (OEL C/STEL) [ppm]	3 ppm
Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Triethylamin
AGW (OEL TWA) [1]	4,2 mg/m ³
AGW (OEL TWA) [2]	1 ppm
Peak exposure limitation factor	2(l)
Remark	DFG;EU;H;6
Regulatory reference	TRGS900
Netherlands - Occupational Exposure Limits	
Local name	Triethylamine
MAC-TGG (OEL TWA)	4,2 mg/m ³
MAC-15 (OEL STEL)	12,6 mg/m ³
Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2020
Poland - Occupational Exposure Limits	
Local name	Trietyloamina
NDS (OEL TWA)	3 mg/m ³
NDSCh (OEL STEL)	9 mg/m ³
Remark (PL)	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286
Spain - Occupational Exposure Limits	
Local name	Trietilamina
VLA-ED (OEL TWA) [1]	8,4 mg/m ³
VLA-ED (OEL TWA) [2]	2 ppm
VLA-EC (OEL STEL)	12,6 mg/m ³
VLA-EC (OEL STEL) [ppm]	3 ppm
Notes	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), f (Reacciona con agentes nitrosantes que pueden dar lugar a la formación de N-Nitrosaminas carcinógenas), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate (55406-53-6)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	3-Iod-2-propinyl-butylcarbamat
AGW (OEL TWA) [1]	0,058 mg/m ³
AGW (OEL TWA) [2]	0,005 ppm
Peak exposure limitation factor	2(l)
Remark	DFG;Y;Sh;11
Regulatory reference	TRGS900
kaolin (1332-58-7)	
Poland - Occupational Exposure Limits	
Local name	Kaolin
NDS (OEL TWA)	10 mg/m ³ frakcja wdychalna
Remark (PL)	Frakcja wdychalna – frakcja aerozolu wnikająca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia. Obowiązuje jednocześnie oznaczanie stężeń frakcji respirabilnej krzemionki krystalicznej.
Regulatory reference	Dz. U. 2018 poz. 1286
silicon dioxide, amorphous (7631-86-9)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Kieselsäuren, amorphe
AGW (OEL TWA) [1]	4 mg/m ³ (E)
Remark	DFG;2;Y
Regulatory reference	TRGS900
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
France - Occupational Exposure Limits	
Local name	Titane (dioxyde de), en Ti
VME (OEL TWA)	10 mg/m ³
Note (FR)	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Poland - Occupational Exposure Limits	
Local name	Ditlenek tytanu
NDS (OEL TWA)	10 mg/m ³ frakcja wdychalna
Remark (PL)	Frakcja wdychalna – frakcja aerozolu wnikająca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia. Obowiązuje jednocześnie oznaczanie stężeń frakcji respirabilnej krzemionki krystalicznej.
Regulatory reference	Dz. U. 2018 poz. 1286
Spain - Occupational Exposure Limits	
Local name	Dióxido de titanio
VLA-ED (OEL TWA) [1]	10 mg/m ³
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

MONO PROPYLENE GLYCOL (57-55-6)	
Poland - Occupational Exposure Limits	
Local name	Propano-1,2-diol
NDS (OEL TWA)	100 mg/m ³ pary i frakcja wdychalna
Remark (PL)	Frakcja wdychalna – frakcja aerozolu wnikająca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia.
Regulatory reference	Dz. U. 2018 poz. 1286
(2-methoxymethylethoxy)propanol (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	(2-Methoxymethylethoxy)-propanol
IOEL TWA	308 mg/m ³
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
France - Occupational Exposure Limits	
Local name	(2-méthoxyméthyléthoxy)-propanol
VME (OEL TWA)	308 mg/m ³
VME (OEL TWA) [ppm]	50 ppm
Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	(2-Methoxymethyl-ethoxy)propanol (Isomerenmischung)
AGW (OEL TWA) [1]	310 mg/m ³
AGW (OEL TWA) [2]	50 ppm
Peak exposure limitation factor	1(l)
Remark	DFG;EU;11
Regulatory reference	TRGS900
Netherlands - Occupational Exposure Limits	
Local name	Dipropyleenglycolmethylether
MAC-TGG (OEL TWA)	300 mg/m ³
Regulatory reference	Arbeidsomstandighedenregeling 2020
Poland - Occupational Exposure Limits	
Local name	(2-Metoksymetyloetoksy)propanol - mieszanina izomerów: 1-(2-metoksy-1-metyloetoksy)propan-2-ol, 1-(2-metoksy-2-metyloetoksy)propan-2-ol, 2-(2-metoksy-1-metyloetoksy)propan-1-ol
NDS (OEL TWA)	240 mg/m ³
NDSCh (OEL STEL)	480 mg/m ³
Remark (PL)	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286
Spain - Occupational Exposure Limits	
Local name	Éter metílico de dipropilenglicol

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

(2-methoxymethylethoxy)propanol (34590-94-8)	
VLA-ED (OEL TWA) [1]	308 mg/m ³
VLA-ED (OEL TWA) [2]	50 ppm
Notes	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: white and white-derived colors.
Odour	: No data available
Odour threshold	: No data available
pH	: 7,5 – 9
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: 0 °C
Freezing point	: No data available
Boiling point	: 100 °C
Flash point	: > 60 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: 23 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1,19 – 1,24 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 400 – 500 mPa·s
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve (111-76-2)	
LD50 oral rat	1746 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1322 - 2301
LD50 oral	1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
2-phenoxyethanol (122-99-6)	
LD50 dermal rat	14391 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 2214 mg/kg bodyweight Animal: rabbit, Guideline: other:Draft IRLG (Interagency Regulatory Liaison Group) Guidelines for Selected Acute Toxicity Tests (August. 1979)
LC50 Inhalation - Rat	> 1 mg/l/4h Animal: rat, Guideline: other:OECD 412
cobalt neodecanoate (27253-31-2)	
LD50 oral rat	1098 mg/kg bw/day
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
triethylamine (121-44-8)	
LD50 oral rat	730 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	580 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
LD50 oral rat	64 – 561 mg/kg
LD50 dermal rat	660 mg/kg
LC50 Inhalation - Rat	171 – 2360 mg/m ³
2-methylisothiazol-3(2H)-one (2682-20-4)	
LD50 oral rat	120 mg/kg
LD50 dermal rat	242 – 2000 mg/kg
LC50 Inhalation - Rat	340 µg/m ³
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionylpoly(oxyethylene)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
LD50 oral rat	3230 mg/kg
LD50 dermal rat	3170 mg/kg
3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate (55406-53-6)	
LD50 oral rat	1056 mg/kg bodyweight
LD50 dermal rabbit	2000 mg/kg

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate (55406-53-6)	
LC50 Inhalation - Rat	670 mg/m ³
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LC50 Inhalation - Rat	3,43 mg/l/4h
MONO PROPYLENE GLYCOL (57-55-6)	
LD50 oral rat	22000 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit
(2-methoxymethylethoxy)propanol (34590-94-8)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 19020 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	9510 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Skin corrosion/irritation	: Not classified pH: 7,5 – 9
Serious eye damage/irritation	: Not classified pH: 7,5 – 9
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified
2-phenoxyethanol (122-99-6)	
LOAEL (animal/male, F1)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
LOAEL (animal/female, F1)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
NOAEL (animal/female, F0/P)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
2-phenoxyethanol (122-99-6)	
LOAEL (oral, rat, 90 days)	> 700 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
LOAEL (dermal, rat/rabbit, 90 days)	500 mg/kg bodyweight Animal: rabbit
triethylamine (121-44-8)	
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	1,02 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Guideline: OECD Guideline 452 (Chronic Toxicity Studies)

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate (55406-53-6)	
STOT-repeated exposure	Causes damage to organs (larynx) through prolonged or repeated exposure (inhalation).
MONO PROPYLENE GLYCOL (57-55-6)	
NOAEL (subchronic, oral, animal/male, 90 days)	443 mg/kg bodyweight Animal: cat, Animal sex: male
(2-methoxymethylethoxy)propanol (34590-94-8)	
LOAEL (dermal, rat/rabbit, 90 days)	Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: other:KANPOGYO No.700, YAKUHATSU No. 1039.61, and KIKYKU No. 1014.

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.
Not rapidly degradable

2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve (111-76-2)	
LC50 - Fish [1]	1474 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	≈ 1800 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	911 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	1840 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d'

2-phenoxyethanol (122-99-6)	
LC50 - Fish [1]	344 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna

triethylamine (121-44-8)	
LC50 - Fish [1]	24 mg/l Test organisms (species): Oryzias latipes
EC50 72h - Algae [1]	8 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	6,8 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	14 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	7,1 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
LC50 - Fish [1]	190 – 300 µg/l

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
EC50 - Crustacea [1]	7 – 160 µg/l
EC50 72h - Algae [1]	6,3 – 27,3 µg/l
2-methylisothiazol-3(2H)-one (2682-20-4)	
LC50 - Fish [1]	4,77 mg/l
EC50 - Crustacea [1]	1,6 mg/l
EC50 72h - Algae [1]	130 µg/l
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
EC50 - Other aquatic organisms [1]	4 mg/l Test organisms (species): other aquatic crustacea:DM
EC50 72h - Algae [1]	> 9 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
LC50 - Fish [1]	900 µg/l
EC50 72h - Algae [1]	420 – 1680 mg/l
3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate (55406-53-6)	
LC50 - Fish [1]	67 µg/l
EC50 - Crustacea [1]	645 µg/l
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] (13463-67-7)	
LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19,3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27,8 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	\geq 2,92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
MONO PROPYLENE GLYCOL (57-55-6)	
LC50 - Fish [1]	51400 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	51600 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 72h - Algae [1]	19300 mg/l Test organisms (species): Skeletonema costatum
EC50 72h - Algae [2]	24200 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	19100 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [2]	19000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
(2-methoxymethylethoxy)propanol (34590-94-8)	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Poecilia reticulata
EC50 - Other aquatic organisms [1]	1930 mg/l Test organisms (species): other aquatic crustacea:Acartia tonsa
EC50 72h - Algae [1]	> 969 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

(2-methoxymethylethoxy)propanol (34590-94-8)

EC50 96h - Algae [1]	> 969 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	0,5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'
NOEC (chronic)	≥ 0,5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)

Partition coefficient n-octanol/water (Log Pow)	2,37 – 2,77
---	-------------

silicon dioxide, amorphous (7631-86-9)

Partition coefficient n-octanol/water (Log Pow)	0,53 @ 25 °C / pH 7
---	---------------------

MONO PROPYLENE GLYCOL (57-55-6)

Partition coefficient n-octanol/water (Log Pow)	-0,9 – -1,07
---	--------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component

(2-methoxymethylethoxy)propanol (34590-94-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
--	---

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

DIRECTIVE 2004/42/EC on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products:

EU limit value for APLEX AQUA WOODCOAT INDU S BASE WHITE (cat. A/e): 130 g/l.

APLEX AQUA WOODCOAT INDU S BASE WHITE Contains max 14,00 g/l VOC.

15.1.2. National regulations

France	
Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(3) - hazardous for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen : kaolin is listed
SZW-lijst van mutagene stoffen : kaolin is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

Switzerland

CH - VOC (SR 814.018) : 1,381450815 %

15.2. Chemical safety assessment

A chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Abbreviations and acronyms	
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements	
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Acute Tox. Not classified (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Not classified
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements	
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Full text of use descriptors	
PC9a	Coatings and paints, thinners, paint removers
PROC7	Industrial spraying

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]		
Skin Sens. 1	H317	Calculation method
Carc. Not classified		Expert judgment
Aquatic Chronic 3	H412	Calculation method

APLEX AQUA WOODCOAT INDU S BASE WHITE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.