

Optiprimer

Contains no or minimal solvents
 Waterborne spray quality for industrial use

PRODUCT DESCRIPTION

	<p>DRYWOOD Optiprimer is a waterborne matt industrial primer for interior and exterior wooden joinery and other wood constructions.</p> <p>See www.drywood.nl for use of this product in a total paint system.</p>
Certification	BRL 0814 (32998) according to Dutch KOMO certification standard


TECHNICAL DATA

General	DRYWOOD Optiprimer is based on a combination of waterborne binders and can be used as a matt coating system.
Properties	DRYWOOD Optiprimer is a quick drying product, has a good adhesion and excellent blocking properties, has a good combination of surface hardness and scratch resistance and durability. The product has nice filling and leveling properties, is easy to sand and has good paintability.
Colours and packaging	DRYWOOD Optiprimer is available in almost all opaque colours. The product is available in 20, 60, 200, 600 and 1000 liter containers. Shelf-life is at least 12 months in unopened and closed packaging and at frost-free storage. Keep packaging closed airtight after opening.
Density	1.15 - 1.30 kg/l (depending the colour)
Solids content	approx. 38 Vol% (depending the colour)
VOC content	60 - 70 g/l EU-Limit (2004/42/EC annex. II A(d): 130 g/l)
Consumption	appr. 8 m ² /l at 50 µm dry film thickness

APPLICATION

General	<p>DRYWOOD Optiprimer can be applied by airless or airmix spraying on a clean surface, sanded and dry, free of dust and grease at a temperature of at least 8 °C. Drying time depends on layerthickness, temperature, relative humidity and ventilation. Next layers can be applied after at least 4 h drying at min. 15 °C and max. 60 % R.H.</p> <p>See KOMO-certificate for drying conditions or min. 48 h at min. 15 °C and max. 60 % R.H. at 100 µm dry film thickness.</p> <p>Stirr well immediately prior to use and check colour.</p>
Environment	The product has low toxicity to environment, has little smell and is not flammable.
Cleaning	Clean equipment after use with water and soap or other suited cleaners. Dilute with water.
Waste	Material and all related packaging must be disposed in a safe way in accordance with full requirements of local authorities.

SAFETY INFORMATION

	see Material Safety Data Sheet
	<p>PIB nr. 040003NL</p> <p>Revisedatum 06-03-2012</p>
	KOMO certificate BRL 0814 (32998)

0

The above information is given according to our present knowledge. DRYWOOD COATINGS B.V. tries to keep the technical information up-to-date. In case further dates or informations of importance should come to our disposal this technical informations-heet will be updated (see date of issue). We reserve the right to modify paint-formulations, processing-instructions, etc. without previous notice. We can not accept liability for mis use of the product or any loss or damage arising out of such.