

Revision date 27-Mar-2023

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK

WHITE

Supercedes Date: 27-Mar-2023 Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK WHITE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word

None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction EUH210 - Safety data sheet available on request

United Kingdom - BE Page 1/14

SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK

WHITE

Supercedes Date: 27-Mar-2023 Revision Number 1

Revision date 27-Mar-2023

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008	Specific concentration limit (SCL)	REACH registration number
Ethylene glycol	(603-027-00- 1) 203-473-3	107-21-1	0.1- <1	[CLP] STOT RE 2 (H373) Acute Tox. 4 (H302)	-	01-2119456816- 28-XXXX
Titanium dioxide	(022-006-00- 2) 236-675-5	13463-67-7	0.1 - <0.3	[C]	-	01-2119489379- 17-XXXX
1,2-benzisothiazol-3(2H) -one [BIT]	(613-088-00-6) 220-120-9	2634-33-5	0.0025 - <0.01	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)	Skin Sens. 1 :: C>=0.05%	01-2120761540- 60-XXXX
reaction mass of 5-chloro-2-methyl-2H-iso thiazol-3-one and 2-methyl-2H-isothiazol-3 -one (3:1) [C(M)IT/MIT]	611-341-5	55965-84-9	<0.0015	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Eye Dam. 1 :: C>=0.6% Eye Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1 :: C>=0.0015%	01-2120764691- 48-XXXX

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

United Kingdom - BE Page 2 / 14

SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK

WHITE

Supercedes Date: 27-Mar-2023 Revision Number 1

Revision date 27-Mar-2023

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	В
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] - 55965-84-9	

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Show this safety

data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper

eyelids. Consult a doctor.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Ingestion Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never

give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

No information available.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2).

United Kingdom - BE Page 3/14

SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK

WHITE

Supercedes Date: 27-Mar-2023 **Revision Number** 1

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

Revision date 27-Mar-2023

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

See Section 12 for additional Ecological Information. **Environmental precautions**

6.3. Methods and material for containment and cleaning up

Do not scatter spilled material with high pressure water streams. **Methods for containment**

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep from freezing.

Recommended storage

temperature

Do not freeze. Keep at temperatures between 5 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Observe technical data sheet. Other information

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits This product contains titanium dioxide in a non-respirable form. Inhalation of titanium

dioxide is unlikely to occur from exposure to this product

United Kingdom - BE 4 / 14 Page

SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK

WHITE

Supercedes Date: 27-Mar-2023 Revision Number 1

Revision date 27-Mar-2023

Chemical name	European Union	United Kingdom
Ethylene glycol	TWA: 20 ppm	TWA: 10 mg/m ³
107-21-1	TWA: 52 mg/m ³	TWA: 20 ppm
	STEL: 40 ppm	TWA: 52 mg/m ³
	STEL: 104 mg/m ³	STEL: 40 ppm
	*	STEL: 104 mg/m ³
		STEL: 30 mg/m ³
		Sk*
Titanium dioxide	-	TWA: 10 mg/m ³
13463-67-7		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)		
Ethylene glycol (107-21-1)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	106 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	35 mg/m³	

Titanium dioxide (13463-67-7)		
Туре	 Derived No Effect Level (DNEL)	Safety factor
worker	10 mg/m ³	
Long term Local health effects		

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m³	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Ethylene glycol (107-21-1)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer	Dermal	53 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Inhalation	7 mg/m³	
Long term Local health effects			

Titanium dioxide (13463-67-7)			
Туре	Exposure route	Derived No Effect Level	Safety factor
		(DNEL)	
Consumer	Oral	700 mg/kg bw/d	

United Kingdom - BE Page 5 / 14

SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK

WHITE

Supercedes Date: 27-Mar-2023 Revision Number 1

Revision date 27-Mar-2023

Long term Systemic health effects		

1,2-benzisothiazol-3(2H)-one [BIT]	(2634-33-5)		
Туре	Exposure route		Safety factor
		(DNEL)	
Consumer	Inhalation	1.2 mg/m ³	
Long term			
Systemic health effects			
Consumer	Dermal	0.345 mg/kg bw/d	
Long term			
Systemic health effects			

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)	
Ethylene glycol (107-21-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10 mg/l
Marine water	1 mg/l
Freshwater sediment	20.9 mg/kg dry weight
Soil	1.53 mg/kg dry weight
Microorganisms in sewage treatment	199.5 mg/l
Freshwater - intermittent	10 mg/l

Titanium dioxide (13463-67-7)		
Environmental compartment	Predicted No Effect Concentration (PNEC)	
Marine water	0.0184 mg/l	
Freshwater sediment	1000 mg/kg	
Freshwater	0.184 mg/l	
Marine sediment	100 mg/kg	
Soil	100 mg/kg	
Microorganisms in sewage treatment	100 mg/l	
Freshwater - intermittent	0.193 mg/l	

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 μg/l
Marine water	0.403 μg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 μg/l
Marine sediment	4.99 μg/l
Soil	3 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Avoid contact with eyes.

Skin and body protection Wear protective gloves and protective clothing. Avoid contact with skin, eyes or clothing.

Respiratory protection During spraying wear suitable respiratory equipment.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid

United Kingdom - BE Page 6 / 14

SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK

WHITE

Supercedes Date: 27-Mar-2023 Revision Number 1

Revision date 27-Mar-2023

Appearance Paste

Colour See section 1 for more information

Odour Characteristic.

Odour threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Melting point / freezing point = $0 \, ^{\circ}$ C Initial boiling point and boiling = $100 \, ^{\circ}$ C

range

Flammability Not applicable for liquids .

Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available limits

Flash point Not applicable No data available °C

Autoignition temperature No data available None known

Decomposition temperatureNone known

pH 7 -

pH (as aqueous solution) No data available None known

Kinematic viscosity > 21 mm²/s Dynamic viscosity No data available

Water solubilityMiscible in water.None knownSolubility(ies)No data availableNone knownPartition coefficientNo data availableNone knownVapour pressureNo data availableNone knownRelative densityNo data availableNone known

Bulk Density No data available

Liquid Density 1.71

Relative vapour density

No data available

None known

Particle characteristics

Particle SizeNo information availableParticle Size DistributionNo information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

United Kingdom - BE Page 7 / 14

SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK

WHITE

Supercedes Date: 27-Mar-2023 Revision Number 1

Revision date 27-Mar-2023

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Do not freeze.

10.5. Incompatible materials

Incompatible materialsNone known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylene glycol	ATE 500 mg/kg	= 10600 mg/kg (Rattus) =	> 2.5 mg/L (Rat) 6 h
		9530 µL/kg (Oryctolagus cuniculus)	
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
1,2-benzisothiazol-3(2H)-one [BIT]	=670 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	-
reaction mass of 5-chloro-2-methyl-2H-isothiazo I-3-one and	= 53 mg/kg (Rat)	LD50 = 87.12 mg/kg (Oryctolagus cuniculus)	= 0.33 mg/L (Rat) 4h
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

United Kingdom - BE Page 8/14

SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK

WHITE

Supercedes Date: 27-Mar-2023 Revision Number 1

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Revision date 27-Mar-2023

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	Eye			Non-irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	Not a skin sensitiser
Sensitisation			
OECD Test No. 429: Skin	Mouse	Dermal	Not a skin sensitiser
Sensitisation: Local Lymph Node			
Assay			

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

11.2.2. Other information

Other adverse effects No information available.

United Kingdom - BE Page 9/14

SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK

WHITE

Supercedes Date: 27-Mar-2023 Revision Number 1

Revision date 27-Mar-2023

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Ethylene glycol 107-21-1	EC50: 6500 - 13000mg/L (96h, Pseudokirchneri ella subcapitata)		EC50 = 10000 mg/L 16 h EC50 = 620 mg/L 30 min EC50 = 620.0 mg/L 30 min	EC50: =46300mg/L (48h, Daphnia magna)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
1,2-benzisothiazol-3(2 H)-one [BIT] 2634-33-5		LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006		EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	
	EC50 (72h) =0.048 mg/L (Pseudokirchner iella subcapitata) (OECD 201)	, ,	-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability No information available.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	biodegradation	Not readily biodegradable
Biodegradability: CO2 Evolution Tes	t		
(TG 301 B)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Component information	
Chemical name	Partition coefficient
Ethylene glycol	-1.36
1,2-benzisothiazol-3(2H)-one [BIT]	0.7
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	0.7

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

United Kingdom - BE Page 10 / 14

SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK

WHITE

Supercedes Date: 27-Mar-2023 Revision Number 1

Chemical name	PBT and vPvB assessment
Ethylene glycol	The substance is not PBT / vPvB PBT assessment does
	not apply
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does
	not apply
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	The substance is not PBT / vPvB
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

Revision date 27-Mar-2023

environmental legislation.

Contaminated packaging Do not reuse empty containers.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Note: Keep from freezing.

Land transport (ADR/RID)

14.1 UN number or ID number
 14.2 Proper Shipping Name
 14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazards
 Not regulated Not regulated Not regulated Not applicable

14.6 Special precautions for user

Special Provisions None

IMDG

14.1UN number or ID numberNot regulated14.2Proper Shipping NameNot regulated14.3Transport hazard class(es)Not regulated14.4Packing groupNot regulated

14.5 Marine pollutant NP

14.6 Special precautions for user

Special Provisions None

14.7 Maritime transport in bulk

according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

United Kingdom - BE Page 11 / 14

SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK

WHITE

Supercedes Date: 27-Mar-2023 Revision Number 1

Revision date 27-Mar-2023

Air transport (ICAO-TI / IATA-DGR)

14.1UN number or ID numberNot regulated14.2Proper Shipping NameNot regulated14.3Transport hazard class(es)Not regulated14.4Packing groupNot regulated14.5Environmental hazardsNot applicable

14.6 Special precautions for user Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide: Contains C(M)IT/MIT (3:1). May produce an allergic reaction

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

United Kingdom - BE Page 12 / 14

SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK

WHITE

Supercedes Date: 27-Mar-2023 Revision Number 1

Revision date 27-Mar-2023

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H411 - Toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'.

In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis

Note V: If the substance is to be placed on the market as fibres (with diameter < 3 μm, length > 5 μm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

Notes relating to the classification and labelling of mixtures

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter \leq 10 μ m

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 27-Mar-2023

United Kingdom - BE Page 13/14

SIROFLEX DECORATORS PREMIUM PAINTABLE CAULK

WHITE

Supercedes Date: 27-Mar-2023 Revision Number 1

Revision date 27-Mar-2023

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 14 / 14