



DECLARATION OF PERFORMANCE
in accordance with Annex III of Regulation (EU) No 305/2011
(Construction Product Regulation)

DoP _ [EN] _ 001 _ Nr. S20141307-0024

1. Unique identification code of product-type:
SX PAINTERS CAULK IT 380ML
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):
Batch number: See product packaging
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:
**Sealant for façade for interior and exterior application
EN 15651-1: F-EXT-INT 12,5P**
4. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):
SIROFLEX LIMITED ■ DODWORTH BUSINESS PARK ■ DODWORTH, BARNSELEY ■ SOUTH YORKSHIRE, S75 3SP
5. Name and contact address of the authorized representative whose mandate covers the task specified in Article 12 (2): not relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3
7. In case of declaration of performance concerning a construction product covered by a harmonized standard:
The notified body 4ward Testing Limited, identification number: 2538 performed the initial type tests under System 3 and issued a report no NLR1797.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: not relevant

Bostik Benelux B.V.
Denariusstraat 11, NL-4903 RC Oosterhout, The Netherlands
Phone: +31 (0)162 491 000, E-mail: info@denbraven.nl
www.denbraven.com



9. Declared performance

Pre-Conditioning: Method A

Substrate: Mortar without primer

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class F	EN 15651-1:2012
Release of chemicals	See product Safety Data Sheet	
Water tightness and air tightness		
Resistance to flow (ISO 7390)	≤ 3 mm	
Loss of volume (ISO 10563)	≤ 25 %	
Adhesion and cohesion properties after immersion in water (ISO10591)	≥ 25 %	
Adhesion and cohesion properties at constant temperature (ISO9046)	NF	

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Vincent Imbos *V. Imbos*
Managing Director
Oosterhout, 03/2020

Bostik Benelux B.V.
Denariusstraat 11, NL-4903 RC Oosterhout, The Netherlands
Phone: +31 (0)162 491 000, E-mail: info@denbraven.nl
www.denbraven.com